SIGMA-ALDRICH

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 5.1 Revision Date 27.07.2016 Print Date 31.10.2016 GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifiers		
1.1	Product identifiers Product name	:	Acetone
	Product Number Brand Index-No. REACH No. CAS-No.	:	650501 Riedel-de-Haen 606-001-00-8 01-2119471330-49-XXXX 67-64-1
1.2	Relevant identified uses	of th	ne substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Manufacture of substances
1.3	1.3 Details of the supplier of the safety data sheet		safety data sheet
	Company	:	Sigma-Aldrich Chemie GmbH Riedstrasse 2 D-89555 STEINHEIM
	Telephone Fax E-mail address	:	+49 89-6513-1444 +49 7329-97-2319 eurtechserv@sial.com
1.4	1.4 Emergency telephone number		er
	Emergency Phone #		0800 181 7059 (CHEMTREC Deutschland) +49 (0)696 43508409 (CHEMTREC weltweit)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 Flammable liquids (Category 2), H225 Eye irritation (Category 2), H319 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal wordDangerHazard statement(s)Highly flammable liquid and vapour.H319Causes serious eye irritation.H336May cause drowsiness or dizziness.

Precautionary statement(s) P210

	eep away from heat, hot surfaces, sparks, open flames and other nition sources. No smoking.
P305 + P351 + P338	IN EYES: Rinse cautiously with water for several minutes. Remove
P370 + P378 In	ontact lenses, if present and easy to do. Continue rinsing. case of fire: Use dry powder or dry sand to extinguish. tore in a well-ventilated place. Keep cool.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	:	C3H6O
Molecular weight	:	58,08 g/mol
CAS-No.	:	67-64-1
EC-No.	:	200-662-2
Index-No.	:	606-001-00-8
Registration number	:	01-2119471330-49-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component		Classification	Concentration
Acetone			
CAS-No.	67-64-1	Flam. Liq. 2; Eye Irrit. 2; STOT	<= 100 %
EC-No.	200-662-2	SE 3; H225, H319, H336	
Index-No.	606-001-00-8		
Registration number	01-2119471330-49-XXXX		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

Extinguishing media 5.1

Suitable extinguishing media Dry powder Dry sand

Unsuitable extinguishing media Do NOT use water jet.

- 5.2 Special hazards arising from the substance or mixture No data available
- 5.3 Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

- 6.3 Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- 6.4 Reference to other sections For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a cool, well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

Components with workplace control parameters

Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Skin contact	Long-term systemic effects	186mg/kg BW/d

Consumers	Ingestion	Long-term systemic effects	62mg/kg BW/d
Consumers	Skin contact	Long-term systemic effects	62mg/kg BW/d
Workers	Inhalation	Acute systemic effects	2420 mg/m3
Workers	Inhalation	Long-term systemic effects	1210 mg/m3
Consumers	Inhalation	Long-term systemic effects	200 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value	
Soil	33,3 mg/kg	ĺ
Marine water	1,06 mg/l	
Fresh water	10,6 mg/l	
Marine sediment	3,04 mg/kg	
Fresh water sediment	30,4 mg/kg	
Onsite sewage treatment plant	100 mg/l	

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Full contact Material: butyl-rubber Minimum layer thickness: 0,3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: butyl-rubber Minimum layer thickness: 0,3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup

to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless		
b)	Odour	No data available		
c)	Odour Threshold	No data available		
d)	рН	No data available		
e)	Melting point/freezing point	Melting point/range: -94,0 °C		
f)	Initial boiling point and boiling range	56,0 °C at 1.013 hPa		
g)	Flash point	-17,0 °C - closed cup		
h)	Evaporation rate	No data available		
i)	Flammability (solid, gas)	No data available		
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 13 %(V) Lower explosion limit: 2 %(V)		
k)	Vapour pressure	533,3 hPa at 39,5 °C 245,3 hPa at 20,0 °C		
I)	Vapour density	No data available		
m)	Relative density	0,79 g/cm3		
n)	Water solubility	completely miscible		
o)	Partition coefficient: n- octanol/water	log Pow: -0,24		
p)	Auto-ignition temperature	465,0 °C		
q)	Decomposition temperature	No data available		
r)	Viscosity	No data available		
s)	Explosive properties	No data available		
t)	Oxidizing properties	No data available		
Oth	Other safety information			
	Surface tension	23,2 mN/m at 20,0 °C		

SECTION 10: Stability and reactivity

10.1 Reactivity No data available

9.2

10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5 Incompatible materials** Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride.

10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5.800 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor. Behavioral:Headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

LC50 Inhalation - Rat - 8 h - 50.100 mg/m3 Remarks: Drowsiness Dizziness Unconsciousness

LD50 Dermal - Guinea pig - 7.426 mg/kg

Skin corrosion/irritation Skin - Rabbit Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation

- Guinea pig Result: Does not cause skin sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard No data available

Additional Information

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fishLC50 - Oncorhynchus mykiss (rainbow trout) - 5.540 mg/l - 96 hToxicity to daphnia and
other aquatic
invertebratesLC50 - Daphnia magna (Water flea) - 8.800 mg/l - 48 hToxicity to algaeRemarks: No data available

12.2 Persistence and degradability Biodegradability Result: 91 % - Readily biodegradable

(OECD Test Guideline 301B)

12.3 Bioaccumulative potential Does not bioaccumulate.

12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1	UN number ADR/RID: 1		IMDG: 1090	IATA: 1090
14.2	ADR/RID:	shipping name ACETONE ACETONE Acetone		
14.3	Transport I ADR/RID: 3	hazard class(es)	IMDG: 3	IATA: 3
14.4	Packaging group ADR/RID: II		IMDG: II	IATA: II
14.5	Environme ADR/RID: n	ntal hazards o	IMDG Marine pollutant: no	IATA: no
14.6	6 Special precautions for user No data available			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.